



Specification of O+ HDPE Electrofusion Service Saddle

O+ HDPE Electrofusion Service Saddle is used to create outlet from main connection line. This Service Saddle is including Bottom plate or without Bottom plate. Made of PE100 material with a precisely molded energized coil of wire, it ensures uniform melting of the strongly electrofused joint and minimizes welding and cooling time.

Products name	HDPE Electrofusion Service Saddle
Sizes Available	DN 63 – 110 x 20mm
SDR	SDR11
PN	PN16
Colors Available	Black

Available Size

EF SADDLE DN 63X20 SDR 11 WITHOUT BOTTEM
EF SADDLE DN 75X20 SDR 11 WITHOUT BOTTEM
EF SADDLE DN 90X20 SDR 11 WITHOUT BOTTEM
EF SADDLE DN 110X20 SDR 11 WITHOUT BOTTEM
EF SADDLE DN 63X20 SDR 11 WITH BOTTEM
EF SADDLE DN 75X20 SDR 11 WITH BOTTEM
EF SADDLE DN 90X20 SDR 11 WITH BOTTEM
EF SADDLE DN 110X20 SDR 11 WITH BOTTEM

Advantages of O+ electrofusion HDPE fittings

O+ can supply various electrofusion HDPE fittings from DN 20 mm to DN 400 mm. HDPE fittings

Advantages: Non-toxic, hygienic: PE pipe fittings are non-toxic and odorless. After strict health monitoring, they are green building materials and never produce scale, which can effectively improve water quality.





- Corrosion resistance: PE is an inert material that is resistant to various chemical media.
- PE pipe fittings are connected by electrofusion, and the interface strength is higher than the pipe itself.
- High toughness: The elongation at break of PE pipe fittings is generally above 500%. For the uneven settlement of the foundation, it has strong adaptability and good seismic performance.
- Excellent resistance to rapid crack propagation (RCP).
- Excellent flexibility and scratch resistance.
- Good wear resistance, low wall friction coefficient, strong conveying capacity.
- Very convenient construction and installation.
- Low system cost and reduced maintenance costs can greatly reduce project costs.
- Long service life: The buried PE pipe fittings are used normally for more than 70 years.
- PE accessories can be reused, fully in line with the advocacy of efficient environmental protection.

Applications of HDPE Electrofusion Fittings

- Municipal water supply, gas supply and agriculture etc.
- Commercial & Residential water supply.
- Industrial liquids transportation.
- Sewage treatment.
- Food and chemical industry.
- Replacement of cement pipes and steel pipes.
- Irrigation Line.

GET IN TOUCH AND REACH US!!

HO & Manufacture Unit:

Oza Piping System Pvt. Ltd

Address: H-23, Behind Latthe Polytechnic College, M.I.D.C Kupwad, Sangli, 416436 Contact: + 91 9890979797

Email: mahesh@hdpe.in
Web. www.hdpe.in

Branch Sales Office:

AURANGABAD

Address: Gut.No.154, Plot 56 Waluj, MIDC Pin - 431136

Contact: + 91 8055951616 Email: <u>prashant@hdpe.in</u> ctcabad@amail.com

Sales Branch:

JAIPUR

Address: D-289, Siddharth Nagar, Malviya Nagar, Pin - 302017

Contact: + 91 8209255214 Email: suresh@hdpe.in Web. www.hdpe.in